

# Universalöle für Traktoren - Huiles universelles pour tracteurs (UTTO)



Artikel Article	Produktname Nom du produit	Viskosität Viscosité [mm <sup>2</sup> /s]		Dichte Densité 15°C [g/cm <sup>3</sup> ]	FP [°C]	PP [°C]	VI	Beschreibung, Spezifikation Description, spécification  VeVa-Code / Code OMD: 13 02 08
		40 [°C]	100 [°C]					
220-8625	Asefarm UTTO JD	41	7.6	0.877	210	-46	156	Universal Tractor Transmission Oil (UTTO)  <b>Getriebe / Transmissions</b> API GL-4 • SAE 75W • MIL-L-2105 <b>Hydraulik / Hydrauliques</b> HVLP, DIN 51524-3, ISO 32-46 <b>Hersteller / Constructeurs</b> JOHN DEERE J20 D • CNH MAT 3505 • I H B – 6 • CASE MS 1207 / 1210 • ZF TE-ML 03F (Einsatz unter - 10°C – application moins -10°C)
220-8652	Asefarm UTTO Plus	59	9.6	0.885	220	-42	144	Universal Tractor Transmission Oil (UTTO)  <b>Getriebe / Transmissions</b> API GL-4 • SAE 80W • MIL-L-2105 <b>Hydraulik / Hydrauliques</b> HVLP, DIN 51524-3, ISO 46-68 <b>Hersteller / Constructeurs</b> JOHN DEERE J20 C • FORD M2C 134 D • NEW HOLLAND FNHA-2-C-201.00 • CNH MAT 3525 • VOLVO WB 101 • MASSEY FERGUSON M1143, M1141, M1129A • WHITE FARM Q 1826 • CASE MS 1206 • KUBOTA UDT STEYR • AGCO-DEUTZ-ALLIS Powerfluid 821 XL • CAT TO-2 • ALLISON C-4 • ZF TE-ML 03E, 05F, 06K
220-8679	Asefarm UTTO FRL	75	11.2	0.889	220	-33	140	Universal Tractor Transmission Oil (UTTO)  <b>Getriebe / Transmissions</b> API GL-4 • SAE 80W • MIL-L-2105 <b>Hydraulik / Hydrauliques</b> HVLP, DIN 51524-3, ISO 68-100 <b>Hersteller / Constructeurs</b> NEW HOLLAND ESN-M2C 86 B, 86 C • MASSEY FERGUSON M 1135 • FIAT • HÜRLIMANN • LAMBORGHINI • LANDINI • RENAULT • FIAT • SAME
220-8627	Asefarm UTTO Special	80	11.4	0.885	220	-36	135	Universal Tractor Transmission Oil (UTTO)  Problemlöser bei Rattergeräuschen / résolution de problèmes de vibration des freins à bain d'huile