

Hydrauliköle - Huiles hydrauliques



Artikel Article	Produktname Nom du produit	Viskosität Viscosité [mm ² /s]		Dichte Densité 15°C [g/cm ³]	FP [°C]	PP [°C]	VI	Test FZG A/8.3/90	Beschreibung, Spezifikation Description, spécification VeVa-Code / Code OMD: 13 01 13
		40 [°C]	100 [°C]						
310-8733	Asehyd HLP 10	10	2.7	0.845	160	-40	105	11	Hochleistungs-Hydrauliköle Huiles hydrauliques à haut rendement • DIN 51524 Teil 2 HLP • ISO 6743/4 L-HM • AFNOR NFE 48-603 HM • DENISON HF-1, HF-2, HF-0 • CINCINNATI MILACRON P-68 (ISO 32), P-69 (ISO 68), P-70 (ISO 46) • VICKERS-INDUSTRIEANLAGEN I-286-S, M-2950-S • GM LH-04-1, LH-06-1, LH-15-1 • US STEEL 136, 137 • SVENK STANDARD SS 15 54 34 • RACINE FLÜGEZELLENPUMPEN • MANNESMANN REXROTH HYDROMATIC
310-8514	Asehyd HLP 15	15	3.5	0.855	190	-30	102	11	
310-8734	Asehyd HLP 22	22	4.3	0.863	196	-30	101	11	
310-8735	Asehyd HLP 32	32	5.3	0.872	218	-30	104	11	
310-8736	Asehyd HLP 46	46	6.8	0.876	220	-30	102	11	
310-8737	Asehyd HLP 68	68	8.7	0.882	224	-30	100	11	
310-8738	Asehyd HLP 100	100	11.1	0.890	240	-24	97	11	