

Hydrauliköle - Huiles hydrauliques

Artikel Article	Produktname Nom du produit	Viskosität Viscosité [mm ² /s]		Dichte Densité 15°C [g/cm ³]	FP [°C]	PP [°C]	VI	Test FZG A/8.3/90	Beschreibung, Spezifikation Description, spécification VeVa-Code / Code OMD: 13 01 13
		40 [°C]	100 [°C]						
310-8739	Asehyd HVI 15	15	4.0	0.850	160	-45	168	11	Hochleistungs-Mehrbereichs-Hydrauliköle Huiles hydrauliques multigrades à haut rendement <ul style="list-style-type: none"> • DIN 51524 Teil 3, HVLP • ISO 6743/4 L-HV • AFNOR NFE 48-603 HV • AFNOR NFE 48-690 (trocken) • AFNOR NFE 48-691 (nass) • CINCINNATI MILACRON P-68 (ISO 32), P-69 (ISO 68), P-70 (ISO 46) • DENISON HF-0, HF-1, HF-2 • U.S. STEEL 127, 136 • VICKERS M-2950-S, I-286-S (Mobilanlagen) VeVa-Code / Code OMD: 13 01 13
310-8518	Asehyd HVI 22	22	5.0	0.860	190	-39	168	11	
310-8740	Asehyd HVI 32	32	6.5	0.868	200	-39	163	11	
310-8741	Asehyd HVI 46	46	8.5	0.872	210	-39	163	11	
310-8742	Asehyd HVI 68	68	11.5	0.878	216	-36	163	11	
310-8519	Asehyd HVI 100	100	14.8	0.891	220	-33	155	11	